



## APPLICATION

Suitable for water, steam, oil and gases.

## SPECIFICATION

Dial Size	4 inch, 5 inch and 6 inch
Immersion Length	9 inch for Adjustable Angle 4 inch and 6 inch for Back and Bottom Entry
Accuracy	+/- 1.0% Full Scale
End Connection	1/2 inch BSPT Thread
Dial	Aluminium alloy, black graduations and figure on white background
Measuring Range	0° to 160°C, others range on request
Accessories	Stainless Steel Thermowell (optional)

## MATERIALS

PARTS	MATERIAL
1. Casing	Stainless Steel AISI 304
2. Bulb & Connection	Stainless Steel AISI 304
3. Pointer	Aluminium with black painted

## APPLICATION

Suitable for water, steam, oil and gases.

## SPECIFICATION

Casing Length	150mm, 200mm
Immersion Length	65mm, 100mm, 125mm or 150mm
Accuracy	+/- 1% of Full Scale
End Connection	1/2 inch BSPT Straight or Angle Type
Measuring Range	-30°C to 50°C, others range on request
Accessories	Brass or Stainless Steel Thermowell

## MATERIALS

PARTS	MATERIAL
1. Casing	Gold Coloured Anodized Aluminium
2. Probe & Connection	Brass

## THERMOMETER BIMETER DIAL



**FIG 7TA**  
Every Angle



**FIG 7TD**  
Bottom Entry



**FIG 7TB**  
Back Entry

## THERMOMETER V-LINE INDUSTRIAL



**FIG 7TFS**  
Back Entry



**FIG 7TFD**  
Bottom Entry